



# Fraunhofer

## TESTED<sup>®</sup> DEVICE

igus GmbH  
chainflex CFLG.LB.PUR  
**Report No. IG 2305-1427**

DUPLICATE

Statement of  
Qualification

Product series  
Particle Emission

Customer

igus GmbH  
Spicher Strasse 1a  
51147 Cologne  
Germany

Component tested

Category:

Energy Supply

Subcategory:

Cable Systems

Product name:

chainflex Optical fibre cable CFLG.LB.PUR  
Tested products:

- CFLG.2LB.PUR.62.5/125 (manufacturing date: second quarter of 2022)
- CFLG.12LB.PUR.62.5/125 (manufacturing date: second quarter of 2022)
- CFLG.12LB.PUR.50.5/125 (manufacturing date: second quarter of 2022)

Random sampling of particle emissions (airborne) at representative sites

Standards/Guidelines:

ISO 14644-1, -14  
The norms stated generally refer to the version valid at the time of the tests.

Test devices:

Optical particle counter:  
LasAir II 110 and LasAir III 110 with measuring ranges  $\geq 0.1\text{ }\mu\text{m}$ ,  $\geq 0.2\text{ }\mu\text{m}$ ,  $\geq 0.3\text{ }\mu\text{m}$ ,  $\geq 0.5\text{ }\mu\text{m}$ ,  $\geq 1.0\text{ }\mu\text{m}$  and  $\geq 5.0\text{ }\mu\text{m}$

Test environment parameters:

- Cleanroom Air Cleanliness Class (according to ISO 14644-1):..... ISO 1
- Airflow velocity:.....0.45 m/s
- Airflow pattern:..... vertical laminar flow
- Temperature: .....22 °C  $\pm$  0.5 °C
- Relative humidity: ..... 45 %  $\pm$  5 %

Test procedure parameters:

- Energy chain: ..... E61.29.050.075.0
- Chain bending radius: .....r = 75 mm
- Stroke length:..... s = 820 mm
- Parameter Set 1:..... $v_1 = 0.5\text{ m/s}$ ;  $a_1 = 1.0\text{ m/s}^2$
- Parameter Set 2:..... $v_2 = 1.0\text{ m/s}$ ;  $a_2 = 2.0\text{ m/s}^2$
- Parameter Set 3:..... $v_3 = 2.0\text{ m/s}$ ;  $a_3 = 4.0\text{ m/s}^2$

Test result / Classification

When operated under the specified test conditions, the cable series chainflex Optical fibre cable CFLG.LB.PUR is suitable for use in cleanrooms fulfilling the specifications of the following Air Cleanliness Classes according to ISO 14644-1:

Test parameter(s)	Air Cleanliness Class
$v_1 = 0.5\text{ m/s}$ ; $a_1 = 1.0\text{ m/s}^2$	4
$v_2 = 1.0\text{ m/s}$ ; $a_2 = 2.0\text{ m/s}^2$	2
$v_3 = 2.0\text{ m/s}$ ; $a_3 = 4.0\text{ m/s}^2$	3
Overall result	4

Please note: Transport damages, incorrect installation, aging behavior, etc. can influence the test result.

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

Department of Ultraclean Technology and Micromanufacturing

Nobelstrasse 12  
70569 Stuttgart  
Germany

IG 2305-1427

Report No. first document

--

Report No. current document

on behalf of


Dr.-Ing. Frank Bürger, Project Manager Fraunhofer IPA


Stuttgart, April 17, 2024

Place, date of first document issued

--

Place, current date



 **Fraunhofer**  
IPA

This document only applies to the named product in its original state and is valid for a period of 5 years from the date the first document was issued. The document can be verified under [www.tested-device.com](http://www.tested-device.com).